Version 1.1	Revision Date: 02/10/2015	MSDS Number: 46955-00002	Date of last issue: 01/13/2015 Date of first issue: 01/13/2015
SECTION	1. IDENTIFICATION		
Produ	uct name	: HILLYARD®	I.H.S. Plus Instant Antiseptic Hand Cleanser
Produ	uct code	: HIL0122503	
Manu	facturer or supplier's	details	
Comp	pany name of supplier	: HILLYARD IN	NDUSTRIES, INC.
Addre	ess	: 302 North Fo St. Joseph, M	
Telep	hone	: 1-816-233-13	321 EXT 8285
Emer	gency telephone	: 1-800-424-93	300
Reco	mmended use of the	chemical and rest	rictions on use
Reco	mmended use	: Hand Sanitize	er
Restr	ictions on use	consumers a foreseeable u specifically de exempt from While this ma contains valu proper use of as well as un spills. This SI employees a intended-use	sonal care or cosmetic product that is safe for nd other users under normal and reasonably use. Cosmetics and consumer products, efined by regulations around the world, are the requirement of an SDS for the consumer. aterial is not considered hazardous, this SDS able information critical to the safe handling and the product for industrial workplace conditions usual and unintended exposures such as large DS should be retained and available for nd other users of this product. For specific guidance, please refer to the information he package or instruction sheet.

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification Flammable liquids	: Category 3
Eye irritation	: Category 2A
GHS Label element Hazard pictograms	
Signal Word	: Warning

Version 1.1	Revision Date: 02/10/2015	MSDS Number: 46955-00002	Date of last issue: 01/13/2015 Date of first issue: 01/13/2015
Haza	rd Statements	: H226 Flammabl H319 Causes se	e liquid and vapor. erious eye irritation.
Preca	autionary Statements	No smoking. P233 Keep cont P241 Use explo equipment. P242 Use only r P243 Take prec P264 Wash skir P280 Wear prot Response: P303 + P361 + all contaminated P305 + P351 + for several minu to do. Continue P337 + P313 If attention. Storage: P403 + P235 St Disposal:	y from heat/sparks/open flames/hot surfaces ainer tightly closed. sion-proof electrical/ ventilating/ lighting/ non-sparking tools. autionary measures against static discharge. n thoroughly after handling. ective gloves/ eye protection/ face protection. P353 IF ON SKIN (or hair): Take off immediately d clothing. Rinse skin with water/shower. P338 IF IN EYES: Rinse cautiously with water tes. Remove contact lenses, if present and easy rinsing. eye irritation persists: Get medical advice/ ore in a well-ventilated place. Keep cool. f contents/ container to an approved waste
Othe	r hazards		

Other hazards

Vapors may form explosive mixture with air.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous ingredients

Chemical Name	CAS-No.	Concentration (%)
Ethanol	64-17-5	>= 50 - < 70
Propan-2-ol	67-63-0	>= 1 - < 5

SECTION 4. FIRST AID MEASURES

General advice	 In the case of accident or if you feel unwell, seek medical advice immediately. When symptoms persist or in all cases of doubt seek medical advice.
If inhaled	: If inhaled, remove to fresh air. Get medical attention if symptoms occur.
In case of skin contact	: Wash with water and soap as a precaution.

Version 1.1	Revision Date: 02/10/2015	MSDS Number: 46955-00002	Date of last issue: 01/13/2015 Date of first issue: 01/13/2015			
		Get medical a	ttention if symptoms occur.			
In case of eye contact		 In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lens, if worn. Get medical attention. 				
If swallowed		Get medical a	: If swallowed, DO NOT induce vomiting. Get medical attention if symptoms occur. Rinse mouth thoroughly with water.			
Most important symptoms and effects, both acute and delayed		: Causes seriou	us eye irritation.			
Prote	ction of first-aiders	and use the re	onders should pay attention to self-protection, ecommended personal protective equipment ential for exposure exists.			
Notes	s to physician	: Treat symptor	matically and supportively.			

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	:	Water spray Alcohol-resistant foam Dry chemical Carbon dioxide (CO2)
Unsuitable extinguishing media	:	High volume water jet
Specific hazards during fire fighting	:	Do not use a solid water stream as it may scatter and spread fire. Flash back possible over considerable distance. Vapors may form explosive mixtures with air. Exposure to combustion products may be a hazard to health.
Hazardous combustion prod- ucts	:	Carbon oxides
Specific extinguishing methods	:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray to cool unopened containers. Remove undamaged containers from fire area if it is safe to do so. Evacuate area.
Special protective equipment for fire-fighters	:	In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Version 1.1	Revision Date: 02/10/2015	MSDS Number: 46955-00002	Date of last issue: 01/13/2015 Date of first issue: 01/13/2015
prot	sonal precautions, ective equipment and ergency procedures	Use personal Follow safe ha	ources of ignition. protective equipment. andling advice and personal protective commendations.
Env	ironmental precautions	Prevent furthe Prevent sprea barriers). Retain and dis	o the environment must be avoided. er leakage or spillage if safe to do so. Iding over a wide area (e.g. by containment or oil spose of contaminated wash water. ies should be advised if significant spillages Itained.
	hods and materials for ainment and cleaning up	Soak up with Suppress (kno jet. For large spill containment t can be pumpe container. Clean up rem absorbent. Local or natio disposal of thi employed in t determine wh Sections 13 a	tools should be used. inert absorbent material. ock down) gases/vapors/mists with a water spray s, provide diking or other appropriate o keep material from spreading. If diked material ed, store recovered material in appropriate aining materials from spill with suitable nal regulations may apply to releases and s material, as well as those materials and items ne cleanup of releases. You will need to ich regulations are applicable. nd 15 of this SDS provide information regarding r national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures	: See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
Local/Total ventilation	: Use with local exhaust ventilation. Use only in an area equipped with explosion proof exhaust ventilation.
Advice on safe handling	 Do not breathe vapors or spray mist. Do not swallow. Do not get in eyes. Avoid prolonged or repeated contact with skin. Handle in accordance with good industrial hygiene and safety practice. Non-sparking tools should be used. Keep container tightly closed. Keep away from heat and sources of ignition. Take precautionary measures against static discharges. Take care to prevent spills, waste and minimize release to the environment.
Conditions for safe storage	: Keep in properly labeled containers.

Version	Revision Date:	MSDS Number:	Date of last issue: 01/13/2015
1.1	02/10/2015	46955-00002	Date of first issue: 01/13/2015
Mater	ials to avoid	Store in accord Keep away fror Do not store wi Strong oxidizing Organic peroxic Flammable soli Pyrophoric liqui Self-heating su	well-ventilated place. ance with the particular national regulations. n heat and sources of ignition. th the following product types: g agents des ds ds ds ds ds ds ds ds ds ds ds ds ds

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Ethanol	64-17-5	TWA	1,000 ppm 1,900 mg/m3	NIOSH REL
		TWA	1,000 ppm 1,900 mg/m3	OSHA Z-1
		STEL	1,000 ppm	ACGIH
Propan-2-ol	67-63-0	TWA	200 ppm	ACGIH
		STEL	400 ppm	ACGIH
		TWA	400 ppm 980 mg/m3	NIOSH REL
		ST	500 ppm 1,225 mg/m3	NIOSH REL
		TWA	400 ppm 980 mg/m3	OSHA Z-1

Ingredients with workplace control parameters

Biological occupational exposure limits

Ingredients	CAS-No.	Control parameters	Biological specimen	Sam- pling time	Permissible concentratio n	Basis
Propan-2-ol	67-63-0	Acetone	Urine	End of shift at end of work- week	40 mg/l	ACGIH BEI
Engineering measures	: Mir	nimize workpla	ce exposure	concentrat	tions.	

Engineering measures

iviinimize workplace exposure concentrations. Use only in an area equipped with explosion proof exhaust ventilation. Use with local exhaust ventilation.

Version	Revision Date:	MSDS Number:	Date of last issue: 01/13/2015
1.1	02/10/2015	46955-00002	Date of first issue: 01/13/2015

Personal protective equipment

Respiratory protection	: General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.
Hand protection Material	: Impervious gloves
Material	: Flame retardant gloves
Remarks	: Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.
Eye protection	: Wear the following personal protective equipment: Safety goggles
Skin and body protection	 Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential. Wear the following personal protective equipment: Flame retardant antistatic protective clothing. Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).
Hygiene measures	 Ensure that eye flushing systems and safety showers are located close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	liquid
Color	:	clear, Colorless to pale yellow

Versi 1.1	ion	Revision Date: 02/10/2015		DS Number: 55-00002	Date of last issue: 01/13/2015 Date of first issue: 01/13/2015
(Odor		:	citrus	
(Odor Tl	hreshold	:	No data available)
F	pН		:	6.0 - 9.2	
I	Melting	point/freezing point	:	No data available)
	Initial b range	oiling point and boiling	:	No data available	•
I	Flash p	oint	:	25 °C	
I	Evapora	ation rate	:	No data available)
I	Flamma	ability (solid, gas)	:	Not applicable	
ι	Upper e	explosion limit	:	No data available)
I	Lower e	explosion limit	:	No data available)
١	Vapor p	pressure	:	No data available)
I	Relative	e vapor density	:	No data available)
I	Density	,	:	0.89 g/cm3	
\$	Solubili Wate	ty(ies) er solubility	:	soluble	
	Partition octanol	n coefficient: n- /water	:	Not applicable	
1	Autoign	ition temperature	:	No data available)
[Decom	position temperature	:	The substance or	r mixture is not classified self-reactive.
Ň	Viscosi Visco	ty osity, kinematic	:	1,000 - 35,000 m	m2/s (20 °C)
I	Explosi	ve properties	:	Not explosive	
(Oxidizir	ng properties	:	The substance or	r mixture is not classified as oxidizing.

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Not classified as a reactivity hazard.	
Chemical stability	: Stable under normal conditions.	
Possibility of hazardous reac-	: Flammable liquid and vapor.	

Version 1.1	Revision Date: 02/10/2015	MSDS Number: 46955-00002	Date of last issue: 01/13/2015 Date of first issue: 01/13/2015
tions			orm explosive mixture with air. strong oxidizing agents.
Cond	itions to avoid	: Heat, flames a	ind sparks.
Incon	npatible materials	: Oxidizing ager	nts
Haza produ	rdous decomposition	: No hazardous	decomposition products are known.

mg/kg

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes	Information on likely routes of exposure						
Skin contact Ingestion Eye contact							
Acute toxicity							
Not classified based on availa	ble	information.					
Product:							
Acute oral toxicity	:	Acute toxicity estimate: > 5,000 Method: Calculation method					
Ingredients:							
Ethanol:							
Acute oral toxicity	:	LD50 (Rat): > 5,000 mg/kg					
Acute inhalation toxicity	:	LC50 (Rat): 124.7 mg/l Exposure time: 4 h Test atmosphere: vapor					
Propan-2-ol:							
Acute oral toxicity	:	LD50 (Rat): > 5,000 mg/kg					
Acute inhalation toxicity	:	LC50 (Rat): 72.6 mg/l Exposure time: 4 h Test atmosphere: vapor					
Acute dermal toxicity	:	LD50 (Rat): > 5,000 mg/kg					
Skin corrosion/irritation							

Skin corrosion/irritation

Not classified based on available information.

Product:

Result: No skin irritation

Ingredients:

Ethanol: Species: Rabbit Method: OECD Test Guideline 404

Version	Revision Date:	MSDS Number:	Date of last issue: 01/13/2015
1.1	02/10/2015	46955-00002	Date of first issue: 01/13/2015

Result: No skin irritation

Propan-2-ol:

Species: Rabbit Result: No skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Ingredients:

Ethanol: Species: Rabbit Result: Irritation to eyes, reversing within 21 days Method: OECD Test Guideline 405

Propan-2-ol:

Species: Rabbit Result: Irritation to eyes, reversing within 21 days

Respiratory or skin sensitization

Skin sensitization: Not classified based on available information. Respiratory sensitization: Not classified based on available information.

Product:

Assessment: Does not cause skin sensitization.

Ingredients:

Ethanol:

Test Type: Local lymph node assay (LLNA) Routes of exposure: Skin contact Species: Mouse Result: negative

Propan-2-ol:

Test Type: Buehler Test Routes of exposure: Skin contact Species: Guinea pig Method: OECD Test Guideline 406 Result: negative

Germ cell mutagenicity

Not classified based on available information.

Ingredients:

Ethanol: Genotoxicity in vitro	:	Test Type: In vitro mammalian cell gene mutation test Result: negative
Genotoxicity in vivo	:	Test Type: Rodent dominant lethal test (germ cell) (in vivo) Species: Mouse Application Route: Ingestion

ersion 1	Revision Date: 02/10/2015	MSDS N 46955-0		Date of last issue: 01/13/2015 Date of first issue: 01/13/2015
		Resu	ılt: negative)
	i n-2-ol: oxicity in vitro		Type: Bact Ilt: negative	erial reverse mutation assay (AMES)
Genot	oxicity in vivo	cytog Spec Appli	enetic ass ies: Mouse	te: Intraperitoneal injection
Carcin	nogenicity			
Not cla	assified based on availa	ble inform	nation.	
Specie Applic Expos Metho	in-2-ol: es: Rat ation Route: inhalation (sure time: 104 weeks id: OECD Test Guideline t: negative			
IARC		equal to		is product present at levels greater than or entified as probable, possible or confirmed by IARC.
OSHA	A		0.1% is id	is product present at levels greater than or entified as a carcinogen or potential carcino
NTP			0.1% is id	is product present at levels greater than or entified as a known or anticipated carcinoge
-	oductive toxicity assified based on availa	bla inform	ation	
	dients:			
Ethan		Spec Appli Meth	ies: Mouse cation Rou	te: Ingestion Test Guideline 416
	n -2-ol: s on fertility	Spec Appli	ies: Rat	-generation reproduction toxicity study te: Ingestion
Effect	s on fetal development	: Test	Type [.] Emb	ryo-fetal development

Version	Revision Date:	MSDS Number:	Date of last
1.1	02/10/2015	46955-00002	Date of first

Date of last issue: 01/13/2015 Date of first issue: 01/13/2015

Species: Rat Application Route: Ingestion Result: negative

STOT-single exposure

Not classified based on available information.

Ingredients:

Propan-2-ol: Assessment: May cause drowsiness or dizziness.

STOT-repeated exposure

Not classified based on available information.

Repeated dose toxicity

Ingredients:

Ethanol: Species: Rat NOAEL: 2,400 mg/kg Application Route: Ingestion Exposure time: 2 y

Propan-2-ol:

Species: Rat NOAEL: 5000 ppm Application Route: inhalation (vapor) Exposure time: 104 w Method: OECD Test Guideline 413

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity		
Ingredients: Ethanol: Toxicity to fish	: LC50 (Pimephales promelas (fathead minnow)): > 1,000 mg/l Exposure time: 96 h	
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): > 1,000 mg/l Exposure time: 48 h	
Toxicity to algae	: EC50 (Chlorella vulgaris (Fresh water algae)): 275 mg/l Exposure time: 72 h Method: OECD Test Guideline 201	
Toxicity to daphnia and other aquatic invertebrates	: NOEC (Daphnia magna (Water flea)): 9.6 mg/l Exposure time: 9 d	

SAFETY DATA SHEET

HILLYARD® I.H.S. Plus Instant Antiseptic Hand Cleanser

ersion .1	Revision Date: 02/10/2015		SDS Number: 955-00002	Date of last issue: 01/13/2015 Date of first issue: 01/13/2015
(Chror	nic toxicity)			
Toxicit	ty to bacteria	:	EC50 (Photobac Exposure time: (terium phosphoreum): 32.1 mg/l).25 h
	Propan-2-ol: Toxicity to fish		LC50 (Pimephal Exposure time: 9	es promelas (fathead minnow)): 10,000 mg/ 96 h
	ty to daphnia and other c invertebrates	:	: EC50 (Daphnia magna (Water flea)): > 10,000 mg/l Exposure time: 24 h	
Toxicit	ty to algae	:	ErC50 (Scenede mg/l Exposure time: 8	esmus quadricauda (Green algae)): > 1,800 3 d
Toxicit	ty to bacteria	:	EC50 (Pseudom Exposure time: 7	onas putida): > 1,050 mg/l l6 h
Persis	stence and degradabil	ity		
	lients:			
Ethan Biode(ol: gradability	:	Result: Readily I Biodegradation: Exposure time: 2	84 %
	n-2-ol: gradability	: Result: rapidly degradable		
Bioac	cumulative potential			
	<u>dients:</u>			
	or: on coefficient: n- ol/water	:	log Pow: -0.35	
Partitio	n -2-ol: on coefficient: n- ol/water	:	log Pow: 0.05	
	ity in soil ta available			
	adverse effects ta available			

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues

: Dispose of in accordance with local regulations.

Version 1.1	Revision Date: 02/10/2015	MSDS Num 46955-0000	
Conta	Contaminated packaging		e of as unused product. containers should be taken to an approved waste g site for recycling or disposal. burn, or use a cutting torch on, the empty drum.
SECTION	14. TRANSPORT INFO	ORMATION	
Intern	ational Regulation		
Class Packir Labels IATA- UN/ID Prope Class Packir Labels Packir aircraf Packir	Imber r shipping name ng group 5 DGR No. r shipping name ng group s ng instruction (cargo it) ng instruction	(Ethano : 3 : III : 3 : UN 198 : Alcohols (Ethano : 3 : III	IOLS, N.O.S. bl, Propan-2-ol) 37
IMDG UN nu Prope Class Packir Labels EmS (r shipping name ng group s		IOLS, N.O.S. bl, Propan-2-ol)
	port in bulk accordin	-	of MARPOL 73/78 and the IBC Code
		Supplied.	
49 CF	stic regulation		

49 CFR UN/ID/NA number Proper shipping name	: UN 1987 : ALCOHOLS, N.O.S.
Class	: 3
Packing group	: III

Version	Revision Date:	MSDS Number:	Date of last issue: 01/13/2015
1.1	02/10/2015	46955-00002	Date of first issue: 01/13/2015
Labels ERG (Marine	-	: FLAMMABLE L : 127 : no	IQUID

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312	Hazards :	Fire Hazard Acute Health Hazard			
SARA 302	:	No chemicals in this materi requirements of SARA Title		reporting	
SARA 313	:	The following components are subject to reporting levels established by SARA Title III, Section 313:		ng levels	
		Propan-2-ol	67-63-0	3.013 %	
US State Regulations					
Pennsylvania Right To Know					
	Ethanol		64-17-5	50 - 70 %	
	Water		7732-18-5	30 - 50 %	
	Propan-2-ol		67-63-0	1 - 5 %	
New Jersey Right To Know					
	Ethanol		64-17-5	50 - 70 %	
	Water		7732-18-5	30 - 50 %	
	Propan-2-ol		67-63-0	1 - 5 %	
California Prop 65		This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.			

The ingredients of this product are reported in the following inventories:AICS: All ingredients listed or exempt.

Inventories


AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), NECSI (Taiwan), TSCA (USA)

VersionRevision Date:MSDS Number:D1.102/10/201546955-00002D

Date of last issue: 01/13/2015 Date of first issue: 01/13/2015

SECTION 16. OTHER INFORMATION

Further information



HMIS III:

HEALTH	2
FLAMMABILITY	3
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High

4 = Extreme, * = Chronic

Full text of other abbreviations

ACGIH		USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI		ACGIH - Biological Exposure Indices (BEI)
NIOSH REL		USA. NIOSH Recommended Exposure Limits
OSHA Z-1		USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim- its for Air Contaminants
ACGIH / TWA	: 8	8-hour, time-weighted average
ACGIH / STEL	: 8	Short-term exposure limit
NIOSH REL / TWA		Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST		STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
OSHA Z-1 / TWA		8-hour time weighted average
Sources of key data used to compile the Material Safety Data Sheet	e	Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen- cy, http://echa.europa.eu/
Revision Date	: (02/10/2015

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8